

SECONDARY DIST.

PRIMARY DIST. (OH)

PRIMARY DIST. (UD)

SPECIALITY DIST.

TRANSMISSION

4x4 Plus® & 2x2 Plus

Cable End Strippers

- For 600 volt secondary cable
- Cutting heads for #6 AWG to 500 kcmil conductors (concentric, compressed or compacted)
- Strips 45 mil to 110 mil secondary insulations
- Choice of square cut or chamfer cut blades
- Strips quickly, even in cold climates
- Guarded cutting blades ensure safety
- Precise stripping with no conductor damage
- Bushings change easily with hex wrench
- Extensions available to strip additional 1.5 in. (38 mm)
- Made in the U.S.A.
- 4 x 4: Length w/ bushings: 4.5 x 5 in. (114 x 127 mm); weight: 14 oz (397 g)
- 2 x 2: Length w/ bushings: 5.75 in. (146 mm); weight: 8 oz (227 g)
- 2x2 Body Part No.: 36101H
- 4x4 Body Part No.: 36001H

4X4 PLUS®



2x2 Plus



Ordering information

1. Select 4 bushings (4 x 4) or two bushings (2 x 2), square or chamfer cut
2. If uncertain, please send cable samples

WS 68

WS 68 SERIES

Power Driven End Strippers

- Ergonomic end stripping tools for 600 volt secondary cable - designed for use with a low or variable speed power drill
- Tools designed to reduce working time and effort on repetitive stripping functions
- New adjustable strip stop with adjustment window allows easy setup for precise strip lengths from 0.625 in. (15.9 mm) to 2.5 in. (63.6 mm)
- Uses standard 2x2 and 4x4 bushings: From #6 AWG to 500 MCM (concentric, compressed, or compacted)
- WS 68 SNAP adds a bushing quick disconnect feature eliminating the need for a hex wrench
- 3/8 in. & 1/2 in. square socket adapters available
- Made in the U.S.A.
- Bushings Sold Separately



WS 68 SNAP

	WS 68	WS 68 SNAP
Drill Adapter(s) Included with tool	1/4 in. (6.35 mm) hex for quick disconnect chucks	3/8 in. (9.5 mm)
Length	6.63 in. (168 mm)	8.5 in. (216 mm) w/ bushing
Weight	10.4 oz (294 g)	1.25 lbs (567.5 g) w/ bushing
Part Number	37430	37955